



# AF90 SMART POS TERMINAL

AF90 is the most elegantly designed and compact secure electronic payment terminal powered by the Android operating system. It comes with a 5.5-inch capacitive Touchscreen, which high-definition display. A wide range of advanced connectivity options are supported, such as 4G/3G/2G, WIFI, Bluetooth, as well as inbuilt NFC contactless, electronic signature capture and massive amounts of memory to enable exceptionally fast processing of applications.

AF90 conforms to UnionPay intelligent terminal safety certification, with multiple tamper and self-destruction mechanism, can be quickly and safely paid.

 Personal financial

 Life service

 Recharge card


 Other

 86 010-61705968

BEIJING SHENZHOU ANFU TECHNOLOGY CO.,LTD

## Advantages

- Support all payment, swiping card, card insertion, NFC, 1D/2D scan code.
- Excellent configuration, large lithium battery, 4G /WIFI/BT
- Android system, can support variety of industry applications.
- Safe and reliable, PCI, PTS, UnionPay UPTS2.0, EMV, PBOC.
- Innovation design, stylish appearance



## Specifications

### Processor

> High performance ARM cortex-a7 - quad core processor, main frequency 1.2GHz

### Operating System

> Android 5.1.1

### Magnetic card reader

> Track 1/2/3, Bi-Directional,  
> Conform to ISO7811

### Smart Card reader

ISO7816、A/B/C Class card

### NFC Reader

> 13.56MHz ,ISO14443 Type A/B  
> Supports Point-to-Point Communication

### Scanning charging base

> Equipped with a base for easy  
> scanning and charging (optional)

### Display

> 5.5 inch TFT  
> Pixel: 1280 \* 720 with backlight

### Touch screen

> 5 touch capacitive screen,  
> support electronic signature

### Port

> 1\*SIM 2\*PSAM

### Camera

> Front-facing camera:300 thousand pixels,  
Fixed focal.  
> Rear camera:5 million pixels,Auto zoom.

### Endurance

>full power state can support 1500 transactions  
of magnetic stripe or financial IC card.  
>in 90 seconds without operation to enter the  
energy saving mode (power saving state).  
> there is no communication and operation for  
10 minutes after the power is opened, and it will  
be automatically closed. If you use it again, you  
need to reboot.

### Physical interface

> 1 MICRO USB interface, 1 MINI USB interface

### GNSS

> GPS/GLONASS/BeiDou

### Printer

> High-Speed Thermal Printer  
> Paper Roll Width/Diameter:58mm/40mm

### Indicator lights

> 1 power indicator light ,4 work indicator lights

### Security

> MK/SK,DUKPT  
> TDES,RSA,SHA256,SM2/SM3/SM4,X9.9/X9.19

### Voltage

> Input: 100-240V AC,50Hz/60Hz  
> Output: 5.0V DC,2.0A  
> Micro-USB Standard Charging Port

### Keypad

> Power button, hot key , volume button + / -

### physical dimension

> 192.7 (L) x 85(W) x 63.4(H) mm

### Battery

> lithium polymer battery; the battery  
can not be exposed in the sun.  
> It can not be put in a place near the fire  
source and can not be put in a too wet place.

### Environmental

> operating temperature: 0-50 C  
> storage temperature: -20 - 70 C  
> humidity: 5% - 90%

### Certification

> EMV L1 & L2  
PBOC 3.0 L1 & L2  
QPBOC L1 & L2  
QUICS  
UPTS2.0  
3C,CE,ROHS  
TE License